

elaboro[®]
think'in ceramics

LiSi LOW FUSE

Micro Layering Glaze & Repair
for Glass Ceramics



Transparent Thin-Layer Glaze
real Lithium Silicate Glass

- Repairs and enhances surfaces of glazes, press ceramics, and LiSi_2
- **no post-processing required**
- Creates a flawless micro-layering finish on zirconia with **LiSi PURE** as basis and **STAINS**

Available as Spray or Pen

The benchmark for Glass Ceramics

LiSi LOW FUSE

LITHIUM SILICATE FOR GLASS CERAMICS
MICRO LAYERING GLAZE & REPAIR


Perfect ceramic surfaces in just one step!

Glazes in veneering systems should smooth the surface and close pores. However, conventional glazes often create

- Blowholes and bubbles
- Rough and abrasive surfaces
- Increased plaque affinity
- Chipping and cracks


Why use elaboro® LiSi LOW FUSE?

SEM analyses show that commercially available glazes are often porous and unstable in use.



elaboro® LiSi LOW FUSE

Apply - Fire - Done



Scientifically proven:

OCT studies show that conventional glazes are not smooth. They tend to form islands, retract from the crown margins and fissures. "Pimples" lead to severe abrasion on the antagonist and early wear damage. Many glazes are prone to optical gray haze or clouding.


elaboro® LiSi LOW FUSE solves these problems!

The innovation

It works so simply

- 1.Application** - Apply powder material by spray or dosing PEN directly to the framework ceramic in a thin layer.
- 2.Firing** - one firing at 800°C is sufficient,
Always follow the instructions in the Instructions for Use.
- 3.Finished** - Perfect high gloss without polish, no reworking, unchanged fittings.

elaboro[®]
think'in ceramics



elaboro[®] LiSi LOW FUSE

Simple - Safe - Sustainable

elaboro[®] LiSi LOW FUSE glazes & repairs in one step!

- Homogeneous transparent, low-stress glass layer
- Brilliant aesthetics without polishing
- Firing at 800°C is gentle on stains
- Closes pores, creates smooth surfaces
- Perfect color reproduction & reliable coverage of crown margins
- Reduced susceptibility to chipping for framework and veneer
- Long-term durability & high plaque resistance

Premium Quality
Made in Germany

LiSi LOW FUSE

LITHIUM SILICATE FOR GLASS CERAMICS
MICRO LAYERING GLAZE & REPAIR

Order Here



NEW!

order now at
www.zirkonshop.de

Easy Application:

1. Apply a thin layer
2. Fire at 800°C (1472°F)
3. Done!



© 2025 Elaboro GmbH
Hagenower Str. 73 | 19061 Schwerin | Germany
tel.: +49 385 3993300 | fax: +49 385 3993302
e-mail: info@elaboro.de | web: www.elaboro.de